

Substrate Notes: It is manufactured as smooth and woodgrain sheets consisting of wood fibres bound with natural lignin. Weathertex is a highly durable exterior grade hard board used for the cladding of residential and commercial buildings. It is 97% timber and 3% natural wax with no glues, resins or formaldehydes. In its **primed form** cladding comes with a 25 year guarantee, and panels come with a 10 year guarantee from the manufacturer. These instructions are to be used with Pre-Primed product only.

Substrate Preparation Notes: Ensure the Weathertex is thoroughly clean and dry before commencing. If there is any doubt, measure moisture content which must be less than 15% before staining or finishing can commence. Examine the surface for the presence of grease, oil, wax, tannin, building marks, or other contaminants. Soap and water may be used where appropriate, then left to dry.

Coating System Summary Weathertex Pre-Primed

Haymes Solashield low Sheen	
1st Coat: LSS	Haymes Solashield Low Sheen
2nd Coat: LSS	Haymes Solashield Low Sheen
Some colours may require additional coats depending on desired levels of opacity.	
<p>Coating Application Details</p> 	<ul style="list-style-type: none"> • Fill nail holes and imperfections with Haymes Unifill. • All surfaces must be clean, bare, dry and free of wax, grease and other contaminants. Methylated spirits may be used where necessary to remove oily contaminants that can interfere with topcoat adhesion. A conspicuous test area should always be performed to check proper adhesion. • If recoating, scrape all loose/flaking paint. Sand smooth & dust down. Surface will require re-priming if surface preparation requires sanding back to bare substrate. • Stir thoroughly before and during application using a broad flat stirrer. • Solashield may be applied on broad wall areas with a 10-12mm synthetic roller and laid off with a brush to provide best results. Apply along the length of the board including all exposed edges and end grain. • Apply 2 coats of Solashield to pre-primed Weathertex timber • Do NOT apply if ambient temperature is less than 10°C or greater than 30°C or if conditions will drop below 10°C during the drying period. Under warmer conditions refer to thinning advice. • Do not apply if showers or dew are indicated within 24 hours • All times quoted assume ambient conditions of 25°C and 50% relative humidity. At cooler temperature or higher humidity drying times will be extended. • Please check the colour for accuracy before application. Haymes Paint will not be accountable for the application of incorrect colours. • For further information, please download the data sheet from the Haymes website
CARE & MAINTENANCE	Protect the coating from abrasive contact for seven days. Periodically cleaning the surface with a mild detergent will rejuvenate the surface and extend the service life by removing contaminants which can damage the surface. It is important to reapply Haymes Solashield when the coating begins to show signs of wear.