



Product Specification

Product Name:

PORTER'S PALM BEACH BLACK

PRODUCT DESCRIPTION:

Porter's Palm Beach Black is a water-based, colourfast black stain suitable for most timber types. Palm Beach Black will produce a transparent effect to enhance the grain of timber. This stain is made with the highest quality UV resistant exterior grade pigments that will enhance water resistance and UV protection.

LOCATION:

Interior and exterior.

ENVIRONMENTAL INFORMATION:

Palm Beach Black contains: 43.65g/L VOC's (Volatile Organic Compounds contribute to atmospheric pollution). Palm Beach White contains 23.75g/L VOCs.

The following descriptors have been adopted by APAS (Australian Paint Approval Scheme):

Very High	>250 g/L
High	100 – 249 g/L
Moderate	50 – 99 g/L
Low	5 – 49 g/L
Very Low	<5 g/L

This product is classified as Low VOC by the Australian Paint Approval Scheme.

Porter's Paints use only premium grade raw materials and wherever possible we buy from Australian suppliers. Our manufacturing processes are designed for maximum performance with minimum impact on the environment and user health.

SUGGESTED APPLICATIONS:

Excellent for use on garden furniture, exterior plywood, weatherboard, shingle or interior furniture and floorboards.

COLOUR:

Translucent black.

LIMITATIONS:

Do not apply in high humidity, below 10°C or above 30°C. Do not apply in direct sunlight.

Not suitable for decking and not suitable for treated timber.

PREPARATION:

The substrate should be sanded to expose clean bare timber free from paint, grease, oil, mould and previous coatings. Timber should be dry and free of contaminants. On previously painted surfaces *all* paint must be removed and surface stripped bare and thoroughly sanded before application.

When using Palm Beach Black over exterior timbers that are oily in nature, such as brush box, blackbutt, jarrah, spotted gum and other hardwoods that have a natural oiliness or waxiness, we recommend allowing the timber to weather for at least 3 months. This is to allow the surface grain to open and the surface oils to dry out. Palm Beach Black, being water based, requires an absorbent non-oily substrate.

Prior to application on all exterior timber, clean the surface with a high strength timber cleaner, such as Intergrain® Reviva®, to remove contaminants or residual oils. Follow manufacturer's application instructions and dry times.

If in doubt as to whether to proceed, apply a water bead test. If water beads on the timber surface the substrate may require further weathering or cleaning. If moisture is absorbed into the surface, then proceed with product application.

APPLICATION:

Stir thoroughly prior to use.

Apply Palm Beach Black in the shade. Apply 1 coat by brush, roller or spray, following the grain and ensuring even coverage. No longer than 3 minutes after application, wipe off excess paint with a soft, absorbent cloth so that the crevices

and grain of the timber hold the colour. If required apply a second coat to deepen the colour, using the same method. Touch dry 30 minutes (using this method). Allow 4 hours dry time before applying second coat. Allow to dry 24 hours.

Do not try to achieve greater opacity or depth of colour by the addition of further coats, as a build up of product can cause cracking and flaking of the finish.

COVERAGE RATES:

Covers up to 15m² per litre, depending upon porosity, surface texture and wastage rates. Please note that on weathered or aged timber with an open grain or more absorbent surface, coverage may be decreased.

WASH UP:

Water.

COMPLEMENTARY PRODUCTS:

On appropriate interior surfaces, Porter's Palm Beach Black can be sealed and protected with Porter's Clearcote (coverage 15m² per litre). Allow Palm Beach Black to dry for 72 hours before applying Clearcote. Test before use as a slight colour variation may occur.

PACKAGING:

Porter's Palm Beach Black is available in 1 litre, 4 litre and 10 litre sizes.

STORAGE:

Store in a cool dry area, protected from frost.

PRECAUTIONS:

Keep out of reach of children. Avoid swallowing.
Avoid eye contact. Avoid prolonged skin contact.
Provide adequate ventilation. If accidental contact occurs, rinse immediately with water. Check colour before use.

MANUFACTURER'S/DISTRIBUTOR'S DETAILS:

Porter's Paints
288 Coward St
Mascot NSW 2020
Australia
Phone: (02) 9698-5322
Toll free: 1800 656 664
Fax: (02) 9699-5322
E-mail: enquiries@porters.com.au
Web: www.porterspains.com

Porter's Paints
150 Hutt Park Rd
Gracefield
Lower Hutt 5010
New Zealand
Ph: 0800 672 468