

## Johnstone's Professional Exterior Deck Oil

Exceptionally durable, fast drying, long lasting, water based transparent oil for hard and soft wood decking.

### Coating System Summary: **Natural Weathertex**

<b>Johnstone's Professional Deck Oil</b>	(Available in Natural, Merbau, Jarrah, Walnut and Teak)
1st Coat:	Johnstone's Professional Exterior Deck Oil
2nd Coat:	Johnstone's Professional Exterior Deck Oil
3rd Coat Optional*:	Johnstone's Professional Exterior Deck Oil
<b>Spread Rate:</b>	12m <sup>2</sup> /L per coat
<b>Recoat Time:</b>	Allow a minimum of 1 hour between coats



#### Weathertex Natural Cladding:

##### SURFACE PREPARATION

1. Remove any surface dust and dirt by sweeping and washing down with water.
2. For best results, use Johnstone's Timber Cleaner otherwise move straight to Step 7. Shake the container thoroughly and ensure the Weathertex surface is wet prior to use.  
**Note:** The surface should be cleaned in cooler conditions and out of direct sunlight to avoid the cleaning solution from drying on the Weathertex surface.
3. Dilute 1 part cleaner with 4 parts water in a bucket or tray and apply vigorously to the surface with a stiff bristle broom or brush. Complete this process in sections. Spot cleaning should be avoided to prevent patchy results.
4. Leave the cleaning solution on the surface for a maximum of 10 minutes. If the surface appears to be drying prior to rinse off, lightly dampen with a spray of water to keep the surface damp throughout the cleaning agent's activation process.
5. Rinse the Weathertex surface thoroughly using light pressure. If using a high pressure washer, avoid using the nozzle close to the surface to prevent indentation and deteriorating of the surface from excessive pressures. **IMPORTANT:** Failure to thoroughly remove the cleaner could result in discoloration under transparent finishes.
6. If stubborn stained areas remain, repeat the application in those areas as per instructions above.
7. Allow the surface to dry thoroughly before applying further Johnstone's products.



#### Deck Oil Application:

1. Stir thoroughly with a broad flat paddle before and during use.
2. Do not apply in direct sunlight and on surface temperatures above 30 °C and below 10 °C. If rain is expected within 24 hours, do not apply the product.
3. Apply liberally along the length of the Weathertex boards including exposed edges and end grain, preferably by brush or applicator pad.
4. Apply two coats allowing 1 hour between the first and second coats. For increased durability, longevity and coverage of the 12 month Aqua Protect guarantee\* a third coat should be applied.

#### CARE & MAINTENANCE

Protect the coating from any abrasive contact for at least seven days.

Clean the surface with Johnstone's Timber Cleaner diluted 6:1 to rejuvenate the surface when required. This will extend the service life of our coating by removing contaminants which can damage the surface, such as salts in coastal areas. It is important to recoat the surface when the coating begins to show signs of wear.