

Project: Weathertex – National projects

Substrate: Weathertex - Weathergroove Natural and Pre-primed Panels.
Weathergroove smooth and Woodsman panels

PAGE 1 OF 2
VERSION 2
NOVEMBER 2019

Interior/Exterior: Exterior

Finish / System: Wattyl Solagard® Low Sheen

Product Features

Wattyl Solagard® Low Sheen is a tough and durable exterior paint which offers protection in any weather or climate. Solagard® Low Sheen Total Protection Technology is designed to keep your home or building looking better for longer. Solagard® Low Sheen's gloss level provides the best balance between appearance, dirt resistance and flexibility for greater protection. Ideal system for enhancing the appearance found in the Weathertex Weathergroove smooth or woodsman Natural and pre-primed Panels. Designed to be applied by professional painters for the Commercial and Builders market.

Surface Preparation

Ensure the surface is clean and dry. All loose, peeling and flaking material must be removed with a scraper. Fill holes and cracks with a suitable filling compound, block down, sand to an even finish, dust off. If mould is present, clean surface with household bleach then rinse well with clean water. Powdery, friable surfaces must be washed and rubbed down to a sound surface. On areas where it is not possible to completely remove powdery materials apply Master Prep Surface Binder. Ensure the previously coated surface is in sound condition. Unsound areas should be stripped or sanded back to bare. Treat bare areas with the recommended first coat for the relevant substrate.

Coatings System

	1 st Coat	2 nd Coat	3 rd Coat (Optional*)
	Wattyl Line 11345 SOLAGARD® Low Sheen	Wattyl Line 11345 SOLAGARD® Low Sheen	Wattyl Line 11345 SOLAGARD® Low Sheen
Technical Data Sheet	D4.14	D4.14	D4.14
A.P.A.S. Specification	APAS 0280/3&5	APAS 0280/3&5	APAS 0280/3&5
Australian Standard	AS3730.8	AS3730.8	AS3730.8
Application Method	Brush, roller, spray	Brush, roller, spray	Brush, roller, spray
Thinners/Clean-up	Water	Water	Water
Spreading Rate	16 m ² /litre	16 m ² /litre	16 m ² /litre
Dry Film Thickness	24 microns	24 microns	24 microns
Surface Dry	30 minutes	30 minutes	30 minutes
Recoat	2 hours	2 hours	2 hours

Cautionary Notes 1

FOR PRE-PRIMED PRODUCTS: In accordance with Weathertex's installation manual always paint primed Weathertex Weatherboards and Architectural panels within 60 days of fixing. Failure to observe this requirement may result in poor adhesion of the topcoat and may void both the Wattyl and Weathertex warranty.

Cautionary Notes 2

Caution: Provide adequate ventilation during use. Application should not be carried out if the air temperature or the substrate temperature is below 10°C or above 35°C. The temperature must not fall below 10°C during the drying process.

Recommended Uses

For exterior use only.
For use on properly installed Weathertex Panels only.

Additional Notes

*A third coat must be applied if the 15-year Solagard, Flake, Peel or Blister Warranty is required. For full details on the Solagard Flake, Peel or Blister warranty refer to: www.wattyl.com.au.

Project:	WeatherTex – National projects
-----------------	--------------------------------

Substrate:	WeatherTex - Weathergroove Natural and Pre-primed Panels. Weathergroove smooth and Woodsman panels
-------------------	---

Interior/Exterior:	Exterior
---------------------------	----------

Finish / System:	Wattyl Solagard® Low Sheen
-------------------------	----------------------------

PAGE 2 OF 2
VERSION 2
NOVEMBER 2019

REFER TO PRODUCT TECHNICAL DATA SHEETS AND SAFETY DATA SHEETS FOR FURTHER INFORMATION ON THE PRODUCTS MENTIONED IN THIS SPECIFICATION SHEET

1. This information is provided with respect to the listed Wattyl products. Valspar Paint (Australia) recommends that:

(a) you review the Technical Data Sheets (TDS) and Safety Data Sheets (SDS) before you use or handle the product; (b) the product be used only in accordance with the information provided by Valspar; (c) the product be transported, stored and handled in accordance with the information on the SDS and relevant TDS; and (d) you thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product.

2. The information in this specification sheet was prepared using information gathered during product development. While Valspar endeavours to update this information and maintain the accuracy and currency of its contents, Valspar cannot guarantee that the information provided is wholly comprehensive.

3. Valspar recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information, please contact your nearest Valspar Office.

4. To the full extent permitted by law, Valspar's liability for breach of a condition or warranty implied into the contract for sale between Valspar and you by law is limited at Valspar's election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product.

Wattyl®, Granosite®, Solagard®, Killrust®, Rust-Eater®, Master Prep®, Colour Designer® & Ecotint® are registered trademarks of Valspar Paint (Australia) Pty Ltd ABN 40 000 035 914.

Solver, Solver Ultra are registered trademarks of Valspar (WPC) Pty Ltd ABN 65 007 527 371.

INFORMATION HOTLINE: Ph: 132 101 (AUSTRALIA)